

KR610 Series



KR610



KR611



KR612



KR613

Specifications

	KR610				KR611				KR612				KR613	
	E	E-RS	D	D-RS	E	E-RS	D	D-RS	E	E-RS	D	D-RS		
Proximity	EM 125 KHz		* MF/DF 13.56 MHz		EM 125 KHz		* MF/DF 13.56 MHz		EM 125 KHz		* MF/DF 13.56 MHz		EM 125 KHz * MF / DF 13.56 MHz	
Read Range	Up to 10 cm		Up to 5 cm		Up to 10 cm		Up to 5 cm		Up to 8 cm		Up to 4.5 cm		Up to 10 cm (EM) / Up to 5 cm (MF)	
Reading Time	≤300ms													
Input Port	External LED Control / External Buzzer Control													
Material	ABS+PC with texture													
Output Format	26/34 bits	26 bits	34/66 bits	66 bits	26/34 bits	26 bits	34/66 bits	66 bits	26/34 bits	26 bits	34/66 bits	66 bits	34 bits	
Power/Current	DC 6-14V / Max.70mA													
LED	Red and Green LEDs													
Op.Temperature	-20°C to 65°C(-10° to +70°C)													
Op. Humidity	10% to 90% relative humidity non-condensing													
Beeper	Yes													
Index of Protection	IP65								IP65				IP65	
Dimensions	75x116x16 mm				86x86x16 mm				86x86x20 mm				86x86x16 mm	
Cable length	150 cm													

* MF= Mifare Classic
DF= Mifare Desfire

ZKTECO MIDDLE EAST

PO Box 4323, Al Asayel St, Bay Square, Building 1, Office 502 & 503
Business Bay, Dubai, United Arab Emirates
E-mail: zk_me@zkteco.com | www.zkteco.me

© Copyright 2017. ZKTeco Inc. ZKTeco Logo is a registered trademark of ZKTeco or a related company. All other product and company names mentioned are used for identification purposes only and may be the trademarks of their respective owners. All specifications are subject to change without notice. All rights reserved.

