

# VK07-C52L Kit

## 4-wire Analog Video Intercom Kit for Villa



The VK07-C52L Kit is the comprehensive 4-wire analog video intercom solution which best suited for villas. This comprehensive video intercom kit includes one indoor monitor, one outdoor station, and Installation accessories. When a visitor arrives and rings the call button, you can see who it is, talk to them, and unlock the door with one press. This system not only enhances the convenience of your daily life but also significantly improves your home's security. Plus, with the ZSmart App, you can unlock the door or talk to visitors when you're away from home. Take a step forward to a smarter and safer home with the VK07-C52L Kit.

### Features

#### Outdoor station

- Linux OS for stability and a high level for customization
- Reached IP65 water resistance and dust proof standard
- 1080 Pixel Camera with 120° viewing angle
- Support IR function (0.2 ~ 3 M; 0.01Lux)
- Support motion detection
- Support night vision
- Control door access by IC card (Max. Cap. 1,000 users)
- Support up to 4 indoor monitors / 2 outdoor stations
- Effortless setup and compatible with flush mount (with rain cover) on flat surface

#### Indoor monitor

- Linux OS for stability and a high level for customization
- 7 inch IPS HD touch screen (1024 \* 600)
- Built-in 6 MB storage space
- Support TF card
- Support dual lock control
- Support a maximum of 2 analog security cameras
- Support setting Weather / calendar / standby wallpaper
- Support remote unlocking through ZSmart App
- Effortless setup and compatible with wall mount

Specifications

Outdoor station		Indoor monitor	
Operation System	Linux	Operation System	Linux
Video Compression	H.264	Resolution	1024*600
Camera	1080P	Display Screen	7 inch touch screen
Camera Viewing Angle	120°	Power Supply	DC 15V 1.2A
Visible Range (Night)	0.2 ~ 3 m	Standby Power	≤3W
Power Supply	Power supply by indoor monitor	Operating Power	≤10W
Motion Detection	Support	Use Distance	≤100M
Audio Input	Microphone*1 (Omni-directional)	Language	Chinese,English,German,French, Russian, Spanish, Arabic, Portuguese
Audio Output	Built-in Speaker	TF Card	Max 128GB
Bi-directional Talk	Support	Support Wi-Fi	IEEE 802.11 a/b/g @ 2.4GHz
Authentication Method	IC Card / NFC	Material	Tempered glass panel + ABS plastic
Card Capacity	1,000 (1:N) (Standard)	Supported Mobile App	ZSmart
Ingress Protection Rating	IP65	Installation	Wall mount
Operating Temperature	-30 °C to +60 °C	Dimension (W * H * D)	195 * 132 * 18 (mm)
Operating Humidity	10% to 90% RH (Non-condensing)		
Casing Material	Aluminium Alloy + ABS plastic		
Installation Method	Flush mount (with rain cover) on flat surface		
Dimension (W * H * D)	125 * 52 * 45 (mm)		

Configuration

